



YASKAWA

DECLARATION OF CONFORMITY

Ref.No.P99042

Oct.31,1999

Jul.31, 2001

We declare under our sole responsibility that the product
Inverter series VS mini V7 (VS-606 V7) as listed below

CIMR-V7□ □ 20 P 1 1 2	CIMR-V7□ □ B 0 P 1 1 2	CIMR-V7□ □ □ 0 P 2 1 2 3
CIMR-V7□ □ □ 0 P 4 1 2 3	CIMR-V7□ □ □ 0 P 7 1 2 3	CIMR-V7□ □ □ 1 P 5 1 2 3
CIMR-V7□ □ □ 2 P 2 1 2 3	CIMR-V7□ □ 43 P 0 1 2	CIMR-V7□ □ □ 3 P 7 1 2 3
CIMR-V7□ □ □ 4 P 0 1 2 3	CIMR-V7□ □ □ 5 P 5 1 2 3	CIMR-V7□ □ □ 7 P 5 1 2 3

1. Model A/R - With digital operator (with potentiometer)
B/S - Without digital operator (with blank cover)
C/T - With digital operator (without potentiometer)
(R,S, and T are flat heatsink version)

2. Specifications A - Japanese Version
U - American Version
C - European Version
D to Z - OEM Version (excluding "U")


3. Voltage class 2 - Three - Phase, 200V
B - Single - Phase, 200V
4 - Three - Phase, 400V

to which this declaration relates is in conformity with the following standard

EN50178 1997

following the provisions of Low Voltage Directive 73/23/EEC, as amended by 93/68/EEC.

YASKAWA ELECTRIC CORPORATION
INVERTER PLANT
2-13-1 Nishimiyaichi, Yukuhashi City
Fukuoka Pref, 824 Japan
Jul.31, 2001


Kazuhisa Akieda
General Manager
Inverter Plant

DECLARATION OF CONFORMITY



YASKAWA

Ref.No.P02083

Dec.24, 2002

We declare under our sole responsibility that the product

Inverter series VS mini V7 as listed below

CIMR-V7
 1 2 3 4 5

1 - Model

V7: VS mini V7 series

2 - Type

A /R: With digital operator (with volume)
B /S: Without digital operator (with blank cover)
C /T: With digital operator (without volume)
(R,S, and T are flat heatsink version)

3 - Specifications

A: Japanese standard model C: European standard model U: American standard model
D to Z: OEM Version (excluding "U")

4 - Voltage class

2: Three phase 200V (Model Type 20P1 - 27P5, excluding 23P0)
4: Three phase 400V (Model Type 40P2 - 47P5)
B: Single phase 200V (Model Type B0P1 - B3P7)

5 - Maximum applicable motor capacity

0P1: 0.1kW 0P2: 0.2kW 0P4: 0.4kW 0P7: 0.75kW 1P5: 1.5kW 2P2: 2.2kW
3P0: 3.0kW 3P7: 3.7kW 4P0: 4.0kW 5P5: 5.5kW 7P5: 7.5kW

To which this declaration relates is in conformity with the following standard

The limits and requirements according to product standard

EN61800-3 dd.1996 and EN61800-3+A11 dd.2000-01

Conducted RF emissions (AC mains port)	EN55022(1994) Class B
Radiated RF emissions (Enclosure)	EN55022(1994) Class B
Electrostatic discharge 6kV contact, 8kV Air	EN61000-4-2(1995)
Fast transient common mode	EN61000-4-4(1995)
4kV a.c power input port, 2kV a.c motor output port, 1kV control port	
Slow transients (Surge)	EN61000-4-5, 1995-03
Conducted RF immunity 10Vrms	EN61000-4-6(1996)
Radiated RF immunity (Enclosure) 10V/m	EN61000-4-3(1996)
Radiated RF immunity (Pulse modulated) 10V/m	ENV50204(1995)
Magnetic Field immunity 30A/m	EN61000-4-8(1994)

following the provisions of EMC Directive 89/336/EEC
amended by 91/263/EEC,92/31/EEC,93/68/EEC

YASKAWA ELECTRIC CORPORATION
2-13-1 Nishimiyaichi Yukuhashi City
Fukuoka Pref, 824-8511 Japan
Dec.24, 2002

Tatsumi TSURUTA
General Manager
Drive Business Sector
Motion Control Division